



JOWA SEAGUARD BILGE ALARM

The JOWA SEAGUARD 15ppm Bilge alarm is designed to monitor the effluent from a bilge water separator. The alarm is approved to IMO MEPC 107(49).

There are 2 alarms out signals which are triggered by the ppm oil content of the separators effluent.

The JOWA SEAGUARD has a cleaning function, auto flush, designed to keep the sensor as clean as possible. Auto flush occurs automatically.

The JOWA SEAGUARD log is controlled by a signal from the separator and is saved on a removable SD card.

Sweden
JOWA AB
Tulebovägen 104
S-428 34 Källered
Sweden
Telephone: +46-31 726 54 00
Telefax: +46-31 795 45 40
website: www.jowa.com
e-mail: info@jowa.se

Norway
JOWA NORGE A/S
Solbergveien 22
3057 Solbergelva
Norway
Telephone: +47-3223 6700
Fax: +47-3223 6701
website: www.jowa.no
e-mail: post@jowa.no

Germany
JOWA GERMANY GMBH
Hansestrasse 21 / Haus 2
18182 Rostock-Bentwisch
Germany
Telephone: +49-381 6302 660
Fax: +49-381 6302 641
website: www.jowa.de
e-mail: info@jowa.de

Netherlands
JOWA HOLLAND
Ebweg 61
2991 LS Barendrecht
Netherlands
Telephone: +31(0)180 55 71 33
Fax: +31(0) 180 61 11 27
website: www.jowa-holland.nl
e-mail: post@jowa-holland.nl

USA
JOWA USA, INC.
59 Porter Road
Littleton, MA 01460
USA
Telephone: +1-978 486 98 00
Fax: +1-978 486 01 70
website: www.jowa-usa.com
e-mail: info@jowa-usa.com

Singapore
JOWA (S) PTE., LTD.
93 Lorong N Telok Kurau #05-04
Singapore 425244
Singapore
Telephone: +65-6872 8802
Fax: +65-6872 8896
website: www.jowa.sg
e-mail: jowaspdk@singnet.com.sg

China
**JOWA (Shanghai) Marine
Equipment Co.,Ltd.**
5111 Luo Shan Road,
Pudong New Area
Shanghai 201204
China
Telephone: +86-21-3390 6889/90/91/92
Fax: +86-21-3390 7550
e-mail: jowasha@jowa.com.cn

China
**JOWA (Shaoxing) Environi
Protection Equipment Co.,Ltd.**
3# He Hu Road
Paojiang Industrial Estate
Shaoxing 312071
China
Telephone: +86 575 88179900
Fax: +86 575 88158630

Korea (South)
Jowa Korea Co. Ltd.
1650-6, Song Jung Dong
Gang Seo - Gu
618-819 Busan
South Korea
Telephone: +82-51-831-4911-3
Fax: +82-51-831-4914
website: www.jowakorea.kr
e-mail: info@jowakorea.kr

For many decades now, Jowa has been a trusted and reliable supplier of technical environmental protection equipment to the shipping industry. We can offer every conceivable service for installation, supervision, operation, monitoring and control of Jowa's equipment. You can choose between our own personnel or one of our trained representatives all over the world.

THE JOWA GROUP



Specifications

Range:	0-30ppm, trend up to 40ppm
Approval/Accuracy:	According to IMO MEPC.107(49)
Display	20 x 4 characters LCD with Backlight
Power Supply:	115-230 VAC 50/60Hz Automatic voltage selection
Power Consumption:	<15 VA
Alarm Points 1 + 2: Factory setting 15ppm	Adjustable between 0-15ppm
Alarm 2 Operating delay: (for annunciation purposes)	Adjustable between 0-540 seconds Factory setting 0 seconds
Alarm 1 Operating delay: (for control purposes)	Adjustable between 0-10 seconds Factory setting 0 seconds
System fault alarm:	Red LED light (flashing)
Alarm contact Rating:	Potential free 1 pole change over contacts; 6A/250V
Alarm indication:	In LCD & Red LED light
Output signal:	0 – 20mA or 4 – 20mA for 0 – 40ppm, ext. load max 150 Ω
Sample water pressure:	Nominal 2 bar
Sample Flow:	Nominal. 2l/min depending on pressure
Ambient temperature	+1 to +60 degrees Celsius
Sample water temperature:	+1 to +60 degrees Celsius
Roll:	Up to 45 degrees
Size:	360 x 240 x 150, LxWxD
Degree of protection:	IP 65
Weight:	7,5 kg
Pipe connections:	R ¼" Female

Type approved by: DNV, USCG, RMRS and CCS